minifast ® Cordset Part Number Key

Part Number Keys are to assist in IDENTIFICATION ONLY. Consult factory for catalog items not identified.

W K M 57x - *M

7/8-16UN (*minifast*)

R = Straight
W = Right Angle

Gender

K = Female Connector, Female Threads
S = Male Connector, Male Threads

Coupling Nut Material

(Blank) = Nylon
M = Nickel Plated Brass
V = Stainless Steel

Length in Meters (*)

See page A7 for standard cable lengths.
Consult factory for other lengths.

Protocol

25 = AS-interface®
39 = Data Highway Plus (Blue Hose®)
43/63 = CC-Link
44 = Ethernet (4-pin)
45 = PROFIBUS®-DP
47 = Genius I/O
48 = PROFIBUS®-PA
49 = FOUNDATION™ fieldbus
53 = SDS
57 = DeviceNet™
58 = Seriplex™
66 = Interbus-S
84 = Ethernet (8-pin)

minifast Receptacle Part Number Key

R K F V 57x - *M /NPT

7/8-16UN (*minifast*)

Gender

K = Female Connector, Female Threads
S = Male Connector, Male Threads

Designator for Receptacle

Mounting Style

(Blank) = Front Mount
P = Back Panel Mount

Material

(Blank) = Anodized Aluminum
K = Nylon
V = Stainless Steel

Connection Type

(Blank) = Leads or PCB Pins
L = Solder Cup

Connection Thread

(Blank) = 1/2-14 NPSM Threads
/NPT = 1/2-14 NPT Threads
/14.5 = 1/2-14 NPT Full Length Threads
/14.75 = 3/4-14 NPT Full Length Threads
/M20 = M20 Threads

Length in Meters (*)

See page A7 for standard cable lengths.
Consult factory for other lengths.

Protocol

25 = AS-interface®
39 = Data Highway Plus (Blue Hose®)
43/63 = CC-Link
44 = Ethernet (4-pin)
45 = PROFIBUS®-DP
47 = Genius I/O
48 = PROFIBUS®-PA
49 = FOUNDATION™ fieldbus
53 = SDS
57 = DeviceNet™
58 = Seriplex™
66 = Interbus-S
84 = Ethernet (8-pin)